



32 King St N., Scotland, ON N0E 1R0
519.443.7333 office@fletchertrailers.com
fletchertrailers.com



NEW 2026 TIMPTE 1420 SPLIT TILT

14,000 GVWR 16'+4' FT

OUR PRICE \$22,995 ~~\$28,745~~

Financing at \$144 Bi-Weekly
(Financing Payments include tax)

Hydraulic Split Tilt Deck

Adjustable hydraulic system allows for controlled raising and lowering of the deck when loading/unloading equipment.
12-degree loading angle.

Stationary Deck in the Front

This fixed portion doesn't tilt, making it ideal for hauling items that don't need driven on—like pallets, toolboxes, or materials.

Mechanically Fastened Joints

By building our trailers using mechanically fastened joints we can achieve maximum strength, durability, and longevity out of the aluminum.

Aluminum Construction

Aluminum outperforms steel for trailers with better corrosion resistance, lower maintenance, and improved towing. It's lighter, enhancing fuel efficiency, and TimpTE's advanced techniques ensure superior quality and durability.

Financing:

Based on \$500 down, over 120 months, @ 7.99% interest rate

\$144 Bi-Weekly

includes all taxes, fully open loan OAC

Specifications

GVWR: 14,000 lb.
Payload Capacity: 11,320 lb.
Deck Length: 16ft + 4ft (20 overall)
Deck Width: 82 3/8"
Loading Angle: 12°

Quick View Options

VIN: 03289

Fletcher Trailers is your trusted source for high-quality car haulers, equipment trailers, dump trailers, tilt deck, deckover, and landscape utility trailers. built tough for contractors, motorsports, and commercial landscaping pros. As the exclusive dealer of TimpTE's all-aluminum commercial-grade trailers, we offer unmatched performance, durability, and value across Ontario, Quebec, Nova Scotia, New Brunswick, PEI, and Manitoba. Whether you're searching for flatbed, split-deck, or gooseneck, we've got the right trailer for your job.

Options Included

Standard Features

Overall Width: 102"
Overall Length: 24' 6"
Payload Capacity: 11,320 lbs.
Stationary Deck Length: 4'
Tilt Deck Length: 16'
Tongue Length: 56"
Deck Height: 22"
Loading Angle: 12°
Wheel Size: 16"
Tires: ST225/75R15E - 10 ply
Number of Lug Bolts: 6 per wheel (24)
Axle: Fixed
Suspension: Rubber Torsion
Brakes: Electric Self-Adjusting
Coupler: 2-5/16"
Coupler Position: Adjustable
Jack Style: Side Crank
Jack Rating: 12,000 lbs.
Stake Pockets: 18
Lighting: LED