



32 King St N., Scotland, ON N0E 1R0
519.443.7333 office@fletchertrailers.com
fletchertrailers.com



NEW 2026 TIMPTE 1424 SPLIT TILT

14,000 GVWR 18'+6' FT

OUR PRICE \$25,495 ~~\$31,895~~

Financing at \$159 Bi-Weekly
(Financing Payments include tax)

Hydraulic Split Tilt Deck

Adjustable hydraulic system allows for controlled raising and lowering of the deck when loading/unloading equipment.
12-degree loading angle.

Stationary Deck in the Front

This fixed portion doesn't tilt, making it ideal for hauling items that don't need driven on—like pallets, toolboxes, or materials.

Mechanically Fastened Joints

By building our trailers using mechanically fastened joints we can achieve maximum strength, durability, and longevity out of the aluminum.

Aluminum Construction

Aluminum outperforms steel for trailers with better corrosion resistance, lower maintenance, and improved towing. It's lighter, enhancing fuel efficiency, and TimpTE's advanced techniques ensure superior quality and durability.

Financing:

Based on \$500 down, over 120 months, @ 7.99% interest rate

\$159 Bi-Weekly

includes all taxes, fully open loan OAC

Specifications

GVWR: 14,000 lb.
Payload Capacity: 11,000 lb.
Deck Length: 18ft + 6ft (20 overall)
Deck Width: 82 3/8"
Loading Angle: 11.5°

Quick View Options

VIN: 03332

The 2026 TimpTE 1424 Split Tilt is a commercial-grade aluminum equipment trailer featuring a 14,000 lb GVWR, 18' hydraulic tilt deck, and a 6' stationary front deck for added loading flexibility. With an 11.5° loading angle, electric self-adjusting brakes, and mechanically fastened aluminum construction, this trailer loads smoothly, with no pull out ramps required.

Options Included

Standard Features

Overall Width: 102"
Overall Length: 28' 6" (includes Hitch)
Payload Capacity: 11,320 lbs.
Stationary Deck Length: 6'
Tilt Deck Length: 18'
Tongue Length: 56"
Deck Height: 22"
Loading Angle: 11.5°
Wheel Size: 16"
Tires: ST225/75R15E - 10 ply
Number of Lug Bolts: 6 per wheel (24)
Axle: Fixed
Suspension: Rubber Torsion
Brakes: Electric Self-Adjusting
Coupler: 2-5/16"
Coupler Position: Adjustable
Jack Style: Side Crank
Jack Rating: 12,000 lbs.
Stake Pockets: 18
Lighting: LED